



- WALL CLADDING SYSTEM
- SEALANT JOINT OR STRIP OF VAPOR PERMEABLE MEMBRANE
- 2 LAYERS OF 60 MIN. BUILDING PAPER
- PRE-FINISHED METAL FLASHING (SET IN SEALANT)
- SEALANT JOINT OR STRIP OF VAPOR PERMEABLE MEMBRANE (TO CONTROL AIR LEAKAGE)
- GALVANIZED METAL BRACKET (WHERE REQUIRED TO SUPPORT PROJECTING LEDGE)
- CONSTRUCTION ADHESIVE (BRACKET ONLY)
- DRAINAGE MAT W/ FILTER FABRIC
- 1/2"–3/4" SCRATCH COAT W/ REINFORCING MESH
- MANUFACTURED STONE



THRU-WALL FLASHING

THIS DETAIL IS INTENDED AS A GENERAL GUIDE FOR WOOD FRAMED RESIDENTIAL BUILDINGS. IT IS NOT MEANT TO REPLACE PROJECT SPECIFIC DESIGN BASED ON THE ENVIRONMENTAL CONDITIONS AT THE SITE AND SPECIFIC MATERIALS TO BE UTILIZED IN THE ASSEMBLIES.

<b>RESIDENTIAL MASONRY CONTRACTORS ASSOCIATION</b>	<b>RMCA DETAILS</b> MANUFACTURED STONE VENEER	
	DATE: 3-30-06	SCALE: N.T.S.
	DESIGN:	DRAWING No.:
	DRAWN:	<b>6</b>
	REVIEWED:	